





★ XB-D60



Product Feature

- Support various barcodes such as WeChat and Alipay
- New decoding chip for interpreting various ID and 2D barcodes
- Support Chinese direct transmission of QR code
- Plug and play, easy to set up and quickly match
- Wire life more durable

Product Size



Specification

Performance Parameters

Light Sources: (Aimer)Green color LED, (Illumination)White color LED
Supported ID: Coda bar, Code 39, Code 32 Pharmaceutical(PARAF), Interleaved 2 of 5,
Symbologies: NEC 2 of 5, Code 93, Straight 2 of 5 Industrial, Straight 2 of 5 IATA, Matrix 2 of 5, Code 11, Code 128, GS1-128, UPC-A, UPC-E, EAN/JAN-8, EAN/JAN-13, MSI, GS1 DataBar Omnidirectional, GS1 DataBar Limited, GS1 DataBar Expanded, China Post(Hong Kong 2 of 5), Korea Pos.
2D: Codeblock A, Codeblock F, PDF417, Micro PDF417, GS1 Composite Codes, QR Code, Data Matrix, MaxiCode, Aztec, HANXIN.
Image (Pixels): 640pixels (H) x 480 pixels (V)
Field of View: 39°(Horizontal), 29°(Vertical)
Print Contrast: 20% minimum reflective difference
Motion Tolerances: > 1m/s
Scan Angle: Yaw±65°, Rotation 360°, Pitch±65°
Depth of scan field: Code39(5mil): 7-16cm, Code39(13mil): 7-32cm
QR code (15mil): 3-18cm, Code128(20mil): 6-35cm
Error Rate: 1/5million
Interface: USBz USB-COM,RS232

Physical Parameters

Dimensions: 83.5mm*65.7mm*174.8mm
Material: ABS+PC
Cable Length: 1.8M

Environmental Parameters

Operating Temperature: -20°C~60°C
Storage Temperature: -30°C~70°C
Relative Humidity: 5% ~95% RH(Non-condensing)
Ambient lighting: 0~100000LUX

Electronic Parameters

Working Voltage: DC5V±5% Standby Current: 35mA
Operating Current: 300mA

Application

